



**PRODUCT DATA SHEET**

Date: 12/01/2020

**Spinnaker Coating**  
 518 East Water Street  
 Troy, Oh 45373  
 800 543-9452

**Ultra Matte™ Litho \*\* 4LZ™ \*\* 3.2 mil (45#) LF**

**Item#:** 0043218

----- TRIMLESS PROGRAMS -----

Recommended Print Type(s) to Test	Dist. Ctr	Length	Min. Width	Core
Laser	Troy, Ohio	2.5 K	3"	6"
Flexo	Troy, Ohio	5 K	3"	6"
	Troy, Ohio	10 K	4"	6"
	New York	2.5 K	3"	6"
	New York	5 K	3"	6"
	New York	10 K	4"	6"
	Atlanta	2.5 K	3"	6"
	Atlanta	5 K	3"	6"
	Atlanta	10 K	4"	6"

Facestock: **Ultra Matte™ Litho**

A premium, matte-coated paper featuring superior smudge resistance, high brightness and high opacity. This sheet offers great ink receptivity, and can also be laser printed.

**Typical Value**

Basis Weight:	60 #/3300 ft <sup>2</sup>
Caliper:	3.7 mils
Tensile MD/CD:	35 / 17
Gloss:	10%
Tear MD/CD:	50 / 55 grams
Opacity:	91%
Sheffield Smoothness:	30 SFU
Parker Print:	2.8 microns
Brightness:	89%

Adhesive: **4LZ™**

This acrylic adhesive provides excellent ultimate adhesion to a wide variety of substrates and designed to be compatible with most low-speed and high-speed laser printers.

**Typical Value**

Coat Weight:	13 #/3300 ft <sup>2</sup>
Coat Weight:	19.24 grams/m <sup>2</sup>
Caliper:	.6 mils
Adhesion to Stainless Steel, oz. (90° Peel):	26
Loop Tack, oz.:	43
Service Temperature:	-40 to +250 °F

Minimum Application Temperature: 45 °F

---

Release Liner: **3.2 mil (45#) LF**

The 3.2mil layflat is a bleached white, MG liner designed specifically to be compatible with high and medium speed cut-sheet laser and ink jet printers. This product is well suited for applications requiring a high degree of layflat. A small amount of clay is applied to the backside of the paper to enhance printability.

**Typical Value**

Basis Weight: 45 #/3000 ft<sup>2</sup>  
Caliper: 3.2 mils  
Tensile MD/CD: 35 / 13 #/inch  
Tear MD/CD: 40 / 55 grams  
Opacity: 86%

**Total Product Caliper:** 7.5 mils

**Product Basis Weight Per MMSI:** 257.89 #

**Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

*For application recommendations call 877-210-5104*

*For samples or other questions please call your Sales Representative.*

**Important Notice**

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Coating, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Coating, LLC. Because of the variety of possible applications for Spinnaker Coating's products and the continuing development of new applications, all Spinnaker Coating, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Coating, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 11/23/2020