

## PRODUCT DATA SHEET

Date: 05/08/2024

**Spinnaker** 550 Summit Avenue Troy, Oh 45373 800 543-9452

## Gloss Inkjet Paper \*\* CLD-10 \*\* 40# liner

Item#: 0048483

TRIMLESS PROGRAMS				
Dist. Ctr	Length	Min. Width	Core	
Troy, Ohio	2.5 K	3"	3"	
Troy, Ohio	5 K	3"	3"	
Troy Ohio	10 K	<b>1</b> "	3"	

TODAY EGG DD O CD A MG

Facestock: Gloss Inkjet Paper

This glossy paper is designed to be compatible with most desktop,

roll-to-roll, and wide-format ink jet printers. This sheet delivers excellent photo images, color graphics, and sharp text. It has good

water fastness and wet-rub characteristics.

**Typical Value** 

 Basis Weight:
 64 #/3300 ft²

 Caliper:
 3.9 mils

 Tensile MD/CD:
 32 / 22

 Gloss:
 77%

Tear MD/CD: 69 / 62 grams

Opacity: 88%
Sheffield Smoothness: 34 SFU
Parker Print: 1.5 microns
Brightness: 94%

Adhesive: **CLD-10** An economical cold temperature hot melt adhesive for a broad range of cold

temperature applications needing high initial tack with excellent die cutting and stripping properties. The adhesive performs well when there is light moisture

present during application.

**Typical Value** 

Coat Weight:  $12 \#/3300 \text{ ft}^2$ Coat Weight:  $17.76 \text{ grams/m}^2$ 

Caliper: .5 mils Adhesion to Stainless Steel, oz. (90° Peel): 30 Loop Tack, oz.: 52

Service Temperature: -50 to 145 °F

Minimum Application Temperature: 10 °F Shear (1000g): 60 minutes Release Liner: 40# liner A bleached, calendered liner featuring excellent die cutting and stripping

characteristics. Recommended for use in roll-to-roll applications.

**Typical Value** 

41 #/3000 ft<sup>2</sup> Basis Weight: 2.5 mils Caliper: Tensile MD/CD: 34 / 21 #/inch Tear MD/CD: 34 / 36 grams Opacity: 69 max%

**Total Product Caliper:** 6.9 mils

**Product Basis Weight Per MMSI: 254.95 #** 

**Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

## **Important Notice**

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 01/24/2024