



## PRODUCT DATA SHEET

Date: 12/20/2024

**Spinnaker**  
550 Summit Avenue  
Troy, Oh 45373  
800 543-9452

### DiversiPrint® 60# Gloss Cover-up \*\* MP376SS Permanent \*\* 58# Scored

---

Facestock: **DiversiPrint® 60# Gloss Cover-up**

A cast coated face stock with a mirror finish for superb print reproduction, this sheet is designed to be compatible with most desk top, high speed laser printers and copiers. The added barrier coat makes this sheet ideal for cover-up applications or when increased opacity is required.

Basis Weight:

**Typical Value**

57 #/3300 ft<sup>2</sup>

Caliper:

3.9 mils

Opacity:

>98%

Brightness:

80%

GSM:

206

---

Adhesive: **MP376SS Permanent**

An aggressive, acrylic emulsion general-purpose permanent adhesive designed to cut cleanly while yielding excellent adhesion to a wide variety of surfaces, including corrugated and low energy surfaces. This is the standard permanent adhesive used in stocking sheet items produced with a paper facestock and select film products

Caliper:

**Typical Value**

.7 mils

Service Temperature:

-65 to 180 °F

Minimum Application Temperature:

35 °F

---

Release Liner: **58# Scored**

A liner specifically designed to meet the stringent lay flat requirements of digital sheet print media. Combined with the appropriate face stock and adhesive, this liner is suitable for high speed laser production presses and copiers as well as most desktop models. It is also suitable for certain offset applications.

**Typical Value**

Basis Weight:	58 #/3000 ft <sup>2</sup>
Caliper:	3.8 mils
Tensile MD/CD:	37 / 20 #/inch
Tear MD/CD:	50 / 65 grams
Opacity:	85%

**Total Product Caliper:** 8.4 mils  
**Product Basis Weight Per MMSI:** 254.32 #  
**Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

*For application recommendations call 877-210-5104  
For samples or other questions please call your Sales Representative.*

**Important Notice**

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 08/26/2024